

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (currently amended) An electret condenser microphone for receiving an acoustic wave to be converted to an acoustic signal indicative of said acoustic wave, comprising:

a casing member having a center axis passing therethrough, said casing member including a circular inlet portion, and a cylindrical side portion integrally formed with said inlet portion of said casing member, said side portion of said casing member having a first section close to said inlet portion of said casing member, and a second section remote from said inlet portion of said casing member, said second section of said side portion of said casing member being radially inwardly bent toward said center axis of said casing member;

a printed circuit board in the form of a circular shape and disposed in said casing member to be held in contact with said second section of said side portion of said casing member, said casing member and said printed circuit board collectively forming a cylindrical casing space;

an electrode plate accommodated in said casing space of said casing member;

an electrically insulating member in the form of an annular ring shape and accommodated in the casing space of the casing member to be held in coaxial alignment with the casing member;

an electrically connecting member intervening between said printed circuit board and said electrode plate to have said printed circuit board and said electrode plate electrically connected with each other, said electrically connecting member being partly retained by said electrically insulating member and disposed on and along the circumference of said printed circuit board; and

a diaphragm located between said inlet portion of said casing member and said electrode plate to be spaced apart along said center axis of said casing member from said electrode plate at a predetermined space distance.

Claim 2. (currently amended) An electret condenser microphone as set forth in claim 1, in which further comprises an said electrically insulating member accommodated is in

~~said casing space of said casing member and provided on said printed circuit board, in which said electrode plate is mounted on said electrically insulating member and retained by said electrically insulating member.~~

Claim 3 (original) An electret condenser microphone as set forth in claim 1, which further comprises a diaphragm supporting member accommodated in said casing space of said casing member and supported by said inlet portion of said casing member, in which said diaphragm is mounted on said diaphragm supporting member and supported by said diaphragm supporting member.

Claim 4 (original) An electret condenser microphone as set forth in claim 1, which further comprises an electrically insulating spacer intervening between said electrode plate and said diaphragm to have said electrode plate and said diaphragm spaced apart from each other at said predetermined space distance.

Claim 5 (original) An electret condenser microphone as set forth in claim 1, which further comprises a covering member provided on said inlet portion of said casing member.

Claim 6 (original) An electret condenser microphone as set forth in claim 1, in which said electrode plate and said diaphragm collectively constitute a capacitor unit to generate an electrical capacitance corresponding to the space distance between said electrode plate and said diaphragm under the state that said acoustic wave is transmitted to said diaphragm to have said diaphragm partly oscillated along said center axis of said casing member with respect to said casing member.

Claim 7 (original) An electret condenser microphone as set forth in claim 6, which further comprises a signal converting unit for converting said electrical capacitance generated by said capacitor unit to said acoustic signal indicative of said acoustic wave transmitted to said diaphragm.

Claim 8 (original) An electret condenser microphone as set forth in claim 7, in which said signal converting unit is accommodated in said casing space of said casing member and provided on said printed circuit board to be electrically connected to said electrode plate and said diaphragm, respectively.

Claim 9 (original) An electret condenser microphone as set forth in claim 7, in which said signal converting unit includes a field effect transistor, a chip capacitor and a resistor.

Claim 10 (original) An electret condenser microphone as set forth in claim 1, in which said electrode plate has thereon an electret film opposing and spaced apart along said center axis of said casing member from said inlet portion of said casing member.

Claim 11 (original) An electret condenser microphone as set forth in claim 1, in which said diaphragm is made of an electret film.

Claim 12 (original) An electret condenser microphone as set forth in claim 1, in which said electrically connecting member is in the form of a column shape and has first and second end surfaces under the state that said first end surface is held in contact with said electrode plate, and said second end surface is held in contact with said printed circuit board.

Claim 13 (original) An electret condenser microphone as set forth in claim 1, in which said electrically connecting member is in the form of a channel shape and has first and second end surfaces under the state that said first end surface is held in contact with said electrode plate, and said second end surface is held in contact with said printed circuit board.

Claim 14 (currently amended) An electret condenser microphone for receiving an acoustic wave to be converted to an acoustic signal indicative of said acoustic wave, comprising:

a casing member having a center axis passing therethrough, said casing member including a circular inlet portion, and a cylindrical side portion integrally formed with said inlet portion of said casing member, said side portion of said casing member having a first section close to said inlet portion of said casing member, and a second section remote from said inlet portion of said casing member, said second section of said side portion of said casing member being radially inwardly bent toward said center axis of said casing member;

a printed circuit board in the form of a circular shape and disposed in said casing member to be held in contact with said second section of said side portion of said casing member, said casing member and said printed circuit board collectively forming

a cylindrical casing space;

an electrode plate accommodated in said casing space of said casing member;

an electrically insulating member in the form of an annular ring shape and accommodated in the casing space of the casing member to be held in coaxial alignment with the casing member;

a plurality of electrically connecting members each intervening between said printed circuit board and said electrode plate to have said printed circuit board and said electrode plate electrically connected with each other, said electrically connecting members being partly retained by said electrically insulating member and disposed on and along the circumference of said printed circuit board to be equidistantly spaced apart from one another; and

a diaphragm located between said inlet portion of said casing member and said electrode plate to be spaced apart along said center axis of said casing member from said electrode plate at a predetermined space distance.

Claim 15 (currently amended) An electret condenser microphone as set forth in claim 14, ~~in which further comprises an~~ said electrically insulating member accommodated is ~~in said casing space of said casing member and~~ provided on said printed circuit board, ~~in which said electrode plate is mounted on said electrically insulating member and retained by said electrically insulating member.~~

Claim 16 (original) An electret condenser microphone as set forth in claim 14, which further comprises a diaphragm supporting member accommodated in said casing space of said casing member and supported by said inlet portion of said casing member, in which said diaphragm is mounted on said diaphragm supporting member and supported by said diaphragm supporting member.

Claim 17 (original) An electret condenser microphone as set forth in claim 14, which further comprises an electrically insulating spacer intervening between said electrode plate and said diaphragm to have said electrode plate and said diaphragm spaced apart from each other at said predetermined space distance.

Claim 18 (original) An electret condenser microphone as set forth in claim 14, which further comprises a covering member provided on said inlet portion of said casing member.

Claim 19 (original) An electret condenser microphone as set forth in claim 14, in which said electrode plate and said diaphragm collectively constitute a capacitor unit to generate an electrical capacitance corresponding to the space distance between said electrode plate and said diaphragm under the state that said acoustic wave is transmitted to said diaphragm to have said diaphragm partly oscillated along said center axis of said casing member with respect to said casing member.

Claim 20 (original) An electret condenser microphone as set forth in claim 19, which further comprises a signal converting unit for converting said electrical capacitance generated by said capacitor unit to said acoustic signal indicative of said acoustic wave transmitted to said diaphragm.

Claim 21 (original) An electret condenser microphone as set forth in claim 20, in which said signal converting unit is accommodated in said casing space of said casing member and provided on said printed circuit board to be electrically connected to said electrode plate and said diaphragm, respectively.

Claim 22 (original) An electret condenser microphone as set forth in claim 20, in which said signal converting unit includes a field effect transistor, a chip capacitor and a resistor.

Claim 23 (original) An electret condenser microphone as set forth in claim 14, in which said electrode plate has thereon an electret film opposing and spaced apart along said center axis of said casing member from said inlet portion of said casing member.

Claim 24 (original) An electret condenser microphone as set forth in claim 14, in which said diaphragm is made of an electret film.

Claim 25 (original) An electret condenser microphone as set forth in claim 14, in which each of said electrically connecting members is in the form of a column shape and has first and second end surfaces under the state that said first end surface is held in contact with said electrode plate, and said second end surface is held in contact with said printed circuit board.

Claim 26 (original) An electret condenser microphone as set forth in claim 14, in which each of said electrically connecting members is in the form of a channel shape and has

Appl. No. 09/993,416  
Amdt. Dated November 10, 2005  
Reply to Office action of August 10, 2005

first and second end surfaces under the state that said first end surface is held in contact with said electrode plate, and said second end surface is held in contact with said printed circuit board.